

1

2

3


4

5

6

7


8



FOR EXPLANATION OF DIMENSIONING ETC., SEE BS 8888.  
 UNLESS OTHERWISE STATED:-  
 (1) ALL BURRS & SHARP EDGES TO BE REMOVED BY 0.5 MAX. CHAMFER OR RADIUS. (2) ALL INTERNAL CORNERS TO BE FORMED BY A 0.5/0.2 RADIUS OR CHAMFER. (3) REFERENCES TO STANDARDS & SPECS. INFER LATEST ISSUE. (4) SURFACE ROUGHNESS  $\sqrt{Ra} T.6$  UNLESS OTHERWISE STATED.

© SYSTEMS LTD OWNS THE COPYRIGHT IN THIS DOCUMENT. IT IS SUPPLIED IN CONFIDENCE AND MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT HAS BEEN ISSUED. IT MUST NOT BE REPRODUCED EITHER IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF THE COPYRIGHT HOLDER.

- 2 Flute Carbide Spot Drill
- Overall Length 40mm



01245 260414 - 250910



sales@smarttoolsuk.com



www.smarttoolsuk.com

TITLE:

2 Flute Carbide Spot Drill

DRG No:

020-009-4-45-040

ISSUE:

N.S.N:

CONTRACTOR:

SECURITY CLASSIFICATION:

UNCLASSIFIED

SHEET No 1 OF 1

A

B

C

D

E

A 3